DL ELECTRONIC & ENGINEERING WORKS

HP: 012-712 0138


鼎立电子自动工程

Email : leongveng@gmail.com

Feature

| 1 | Fast arming key |
|----|--|
| 2 | Keypad arm and disarm |
| 3 | Remote control arm and disarm |
| 4 | Programmable siren on time |
| 5 | Programmable number of repeat phone call dial out during alarm |
| 6 | View 3 group of phone number in memory |
| 7 | Dial out 3 group of phone number |
| 8 | View alarm history |
| 9 | Zone 1 entry and exit delay is programmable |
| 10 | 6 zone chime feature |
| 11 | 6 zone wiring test mode |
| 12 | 6 zone bypass mode |
| 13 | 6 vibration sensitivity setting |
| 14 | 6 zone open / short circuit monitor |
| 15 | System maintenance password and user password is programmable |
| 16 | Arm disarm siren's tick volume is programmable |
| 17 | Zone 5 programmable to Emergency input |
| 18 | Zone 6 programmable to AC power fault monitoring |





LWJ88 DI

Sensitive touch key No power is require Multifunction security system

Note

| 1 | Bypass zone is display via LED when arming the system. |
|---|--|
| 2 | When any zone is open, arming is not allow, 4 beep sound on siren |
| 3 | If password is forgotten, disconnect phone line, turn on remote control and connect phone line |
| | 0-LED start flashing, enter 32xxx into keypad, if 10 second is up and no key is enter. |
| | The old password is used |
| | |

Usage

1 6 zone burgle alarm / Elderly panic alarm

2 Machinery failure / Power failure Dialer